NEW RANGE ROVER SPORT ELECTRIC 27MY TECHNICAL SPECIFICATIONS	450 PS	550 PS
Propulsion	Dual-motor electric	
Electric motor type	Permanent magnet front and rear	
Battery type	Lithium-ion Nickel Manganese Cobalt	
Usable energy	118,5 kWh	
Total energy	128.6kWh	
Max Power	330 kW/450 PS	404 kW/550 PS
Max Torque	677 Nm	850 Nm
Transmission and ratios	Single-speed automatic	
Range (TEL Combined)	378miles / 609 km	
Range (TEH Combined)	367miles / 590 km	
Range added in 10 mins (WLTP, 800V at 350kW)	136miles / 220 km	
Range added in 10 mins (WLTP, 400V at 250kW peak)	98miles / 158 km	
Range added in 60 mins (EU, three-phase 22kW AC)	96 km	
10-80% charge time (CCS Rapid DC Charge 800V at 350kW	22 mins	
Onboard charger capacity	22 kW	
Brakes (front/rear mm)	Front four-piston opposed caliper / corrosion resistant ventilated disc: 380 mm Rear single-piston 46 mm sliding / corrosion resistance ventilated disc: 355 mm	
Steering	Electric Power Assisted Steering (EPAS) rack and pinion	
All-wheel drive system	Permanent AWD	
Front suspension	Double Wishbone with Virtual Lower Swivel Axis	
Rear suspension	5-link axle	

EXTERIOR DIMENSIONS		
Overall length (mm)	4946	
Overall height (with antennae) (mm)	1819	
Overall width (mirrors folded) (mm)	2047	
Overall width (mirrors out) (mm)	2209	
Wheelbase (mm)	2997	
Front overhang (mm)	873	
Rear overhang (mm)	1076	
Front track (mm)	1702,2	
Rear track (mm)	1704,3	
Turning Circle - kerb-to-kerb (metres)	12,53 / 10,95***	10,95
Turning Circle - wall-to-wall (metres)	12,94 / 11,42***	11,42
Drag coefficient (Cd)	0,29	

INTERIOR DIMENSIONS	
Headroom (mm)	Row 1 (with sunroof): 985; Row 2 (with sunroof): 990
Shoulderroom (mm)	Row 1: 1545; Row 2: 1500
Legroom (mm)	Row 1: 1024; Row 2: 961
Loadspace length (mm)	Row 1: 1827; Row 2: 970
Loadspace width (mm)	1400
Luggage Capacity (litres)	Row 1: 1814; Row 2: 789
Loadspace door aperture height (mm)	793
Loadspace door aperture width (mm)	Upper: 1021; Lower: 1121

ALL-TERRAIN CAPABILITY	
Approach angle (deg)[1] (Towing Eye Cover Removed)	29,9
Departure angle (deg)[1] (Towing Eye Cover Removed)	29,6
Ramp angle (deg)[1]	22,3
Maximum Wading depth (mm)	900
Maximum ground clearance (mm)[1]	263
Maximum permissable towable mass (kg)	2500
Maximum permissable unbraked towable mass (kg)	750

PERFORMANCE		
0-100 km/h (secs)[2]	5,6	4,5
80-120 km/h (secs)	3,3	2,7
Top speed km/h	200	

WEIGHT	
Unladen Weight (EU) from (kg)	2770

[1] Vehicle in off-road height

[2] Dynamic Launch Engaged

** The 10-80% in 22 minutes charging times with maximum charging power (DC fast charging station with >=325 kW, >=800 V) apply to an ambient tem

*** with Stormer Handling Pack and all wheel steering

Charging times and speed will vary dependent on many factors, including but not limited to: the age, condition, temperature and existing charge of the battery; facility used, ambient condition and duration of charge.

Weights stated reflect vehicle standard specification.

Jaguar Land Rover is constantly seeking ways to improve the specification, design and production of its vehicles, parts and accessories and alterations take place continually. While every effort is made to produce up-to-date literature, this document should not be regarded as an infallible guide to current specifications or availability, nor does it constitute an offer for the sale of any particular vehicle, part or accessory. Figures are manufacturer's estimates