

	SWB		LWB
NEW RANGE ROVER ELECTRIC 27MY SWB TECHNICAL SPECIFICATIONS	450PS	550PS	550PS
Propulsion	Dual-motor electric		Dual-motor electric
Electric motor type	Permanent magnet front and rear		Permanent magnet front and rear
Battery type	Lithium Nickel Manganese Cobalt		Lithium Nickel Manganese Cobalt
Usable energy	118.5kWh		118.5kWh
Max Power	330kW/450PS	405kW/550PS	405kW/550PS
Max Torque	677Nm	850Nm	850Nm
Transmission and ratios	Single-speed automatic		Single-speed automatic
Range (TEL Combined)	372miles / 600km		372miles / 600km
Range (TEH Combined)	362miles / 583km	359miles / 578km	357miles / 574km
Real-world range	Up to 333miles / 535km		Up to 333miles / 535km
Range added in 10 mins (WLTP, 800V at 350kW)	136miles / 220km		136miles / 220km
Range added in 10 mins (WLTP, 400V at 250kW peak)	98miles / 158km		98miles / 158km
Range added in 60 mins (EU, three-phase 22kW AC)	60miles / 96km		60miles / 96km
10-80% charge time (CCS Rapid DC Charge 800V at 350kW)	22mins		22mins
Onboard charger capacity	22kW		22kW
Brakes (front/rear mm)	Front four-piston opposed caliper / corrosion resistant ventilated disc: 380mm Rear single-piston 46mm sliding / corrosion resistance ventilated disc: 355mm		Front four-piston opposed caliper / corrosion resistant ventilated disc: 380mm Rear single-piston 46mm sliding / corrosion resistance ventilated disc: 355mm
Steering	Electric Power Assisted Steering (EPAS) rack and pinion		Electric Power Assisted Steering (EPAS) rack and pinion
All-wheel drive system	Permanent AWD		Permanent AWD
Front suspension	Double Wishbone with Virtual Lower Swivel Axis		Double Wishbone with Virtual Lower Swivel Axis
Rear suspension	5-link axle		5-link axle
EXTERIOR DIMENSIONS			
Overall length (mm)	5052		5252
Overall height (with antennae) (mm)	1867		1870
Overall width (mirrors folded) (mm)	2047		2047
Overall width (mirrors out) (mm)	2209		2209
Wheelbase (mm)	2997		3197
Front overhang (mm)	860		866
Rear overhang (mm)	1195		1195
Front track (mm)	1702.3		1700.3
Rear track (mm)	1704.3		1702.3
Turning Circle - kerb-to-kerb (metres)	10.95		11.54
Turning Circle - wall-to-wall (metres)	11.39		11.96
Drag coefficient (Cd)	0.29		0.29
INTERIOR DIMENSIONS			
Headroom (mm)	Row 1 (with sunroof): 999; Row 2 (with sunroof): 996.5		Row 1 (with sunroof): 999; Row 2 (with sunroof): 978
Shoulderroom (mm)	Row 1: 1545; Row 2: 1500		Row 1: 1545; Row 2: 1500
Legroom (mm)	Row 1: 1013; Row 2: 1027		Row 1: 1013; Row 2: 1220
Loadspace length (mm)	Row 1: 1975.5; Row 2: 1092.6		Row 1: 2165; Row 2: 1093
Loadspace width (mm)	1444		1444
Luggage Capacity (litres)	Row 1: 2210; Row 2: 925		Row 1: 2602; Row 2: 925
Loadspace door aperture height (mm)	845.8		845.8
Loadspace door aperture width (mm)	Upper: 939; Lower: 1120		Upper: 938; Lower: 1120
ALL-TERRAIN CAPABILITY			
Approach angle (deg) ¹ (TEC Removed)	33.2		33.2
Departure angle (deg) ¹ (TEC Removed)	28.1		28.1
Ramp angle (deg) ¹	22.3		20.9
Maximum Wading depth (mm)	900		900
Ground clearance at curb weight (mm)	201		201
Maximum permissible towable mass (kg)	2500		-
Maximum permissible unbraked towable mass (kg)	750		-
PERFORMANCE			
0-60mph (0-96km/h) (secs) ²	5.4	4.3	4.5
0-62mph (0-100km/h) (secs) ²	5.6	4.5	4.7
50-75mph (80-120km/h) (secs)	3.4	2.7	2.9
Top speed mph (km/h)	124 (200)		124 (200)
WEIGHT			
Unladen Weight (EU) from (kg)	2810		2810

¹ Vehicle in off-road height
² Dynamic Launch Engaged

Jaguar Land Rover is constantly seeking ways to improve the specification, design and production of its vehicles, parts and accessories and alterations take place continually. While every effort is made to produce up-to-date literature, this document should not be regarded as an infallible guide to current specifications or availability, nor does it constitute an offer for the sale of any particular vehicle, part or accessory. Figures are manufacturer's estimates